

## 60W Single Output Waterproof Power Supply



Low Cost, High Reliability  
 Low Power Consumption  
 Protections: Over Load/ Short Circuit  
 100% Full Load High Temperature Burn-in Test  
 1 Years Warranty

Input Voltage Range	180~250VAC
Input Frequency	47-63Hz
Inrush Current	Cold Start, 50A/ 230VAC
Line Regulation	0.5%
Output Over Load Protection	105%~150%Hiccup mode, Auto-recovery
Rise, Hold Up Time	100mS, 10mS at Full Load (Typical)
Hi-pot Isolation	I/P-O/P, 1.5KVAC
Working Temperature	0 to+50 @100%,-10 @80%,+60 @60% Load
Storage Temperature	-40 to +85, 0 to 95%RH (Non-Condensing)
Safety Standards	Design Refer To UL1310class2,TUV EN60950-1,EN61347-2-13
EMC standards	Design Refer TO FCC Part 15 J
Cooling Method	Free Air Cooling Convection
Weight	0.8Kgs/pcs
Size	147.5*70*40mm

Product model	DC output	Load regul.	R&N	Efficiency
HTS-05060	5V,0~8A	5%	100mV	72%
HTS-12060	12V, 0~5A	3%	120mV	80%
HTS-15060	15V, 0~4A	2%	150mV	80%
HTS-24060	24V,0~2.5A	2%	240mV	82%
HTS-36060	36V,0~1.67A	1%	360mV	82%
HTS-48060	48V,0~1.25A	1%	480mV	84%