

150W Single Output Waterproof Power Supply



Low Cost, High Reliability

Low Power Consumption

Protections: Over Load/ Short Circuit

100% Full Load High Temperature Burn-in Test

1 Years Warranty

Input Voltage Range	180~250VAC
Input Frequency	47-63Hz
Inrush Current	Cold Start, 50A/ 230VAC
Line Regulation	0.5%
Output Over Load Protection	90%~130% Constant Current, Auto-recovery
Rise, Hold Up Time	100mS, 10mS at Full Load (Typical)
Hi-pot Isolation	I/P-O/P, 1.5KVAC
Working Temperature	0 to+50 @100%,-10 @80%,+60 @60% Load
Storage Temperature	-40 to +85, 0 to 95%RH (Non-Condensing)
Safety Standards	Design Refer To UL1310class2,TUV EN60950-1,EN61347-2-13
EMC standards	Design Refer TO FCC Part 15 J
Cooling Method	Free Air Cooling Convection
Weight	1.1Kgs/pcs
Size	190.5*70*40mm

Product model	DC output	Load regul.	R&N	Efficiency
HTS-12150	12V,0~12.5A	3%	120mV	84%
HTS-15150	15V, 0~10A	2%	150mV	84%
HTS-24150	24V, 0~6.25A	2%	240mV	85%
HTS-36150	36V,0~4.2A	1%	360mV	85%
HTS-48150	48V,0~3.1A	1%	480mV	86%