

Features


DIMENSIONS: 104(H)x76(D)x45(W)mm
WEIGHTS: 190g

- **Din Rail/ Screw Mounting Dual Purpose**
- Convection cooled
- Wide input range
- 100% full load burn-in test
- MOSFET designed
- 350,000Hrs MTBF per MIL-HDBK-217F
- 2-year warranty
- **Output modify range: 3V~200VDC**
- **Split rail & Series connection possible**

General specifications
INPUT

Input range	90~264VAC 127~380VDC
Input frequency	47~63Hz
Inrush current (25° C)	40A/220VAC

OUTPUT

Hold-up time	16mS
Short protection	Autorecovery
Overload protection	Automatic power limited
Over voltage protection	Optional

Detail specifications
20 & 24Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V.P. Trip point
		Min.	Rated	Max.					
RP1020D-05F	V1: +5V ±10%	0A	4.0A	4.0A	50mVp-p	±1%	±1%	60% Min.	6 ~ 7.5V
RP1024D-12F	V1: +12V ±10%	0A	2A	2A	100mVp-p	±1%	±1%	70% Min.	14 ~ 17V
● RP1024D-15F	V1: +15V ±10%	0A	1.6A	1.6A	150mVp-p	±1%	±1%	71% Min.	17 ~ 22V
RP1024D-24F	V1: +24V ±10%	0A	1A	1A	150mVp-p	±1%	±1%	71% Min.	28 ~ 34V

EMC Standards

EN55022 CLASS B, EN55024
EN 61000-3-2 CLASS A
EN 61000-3-3, IEC 61000-4-2
IEC 61000-4-3, IEC 61000-4-4
IEC 61000-4-5, IEC 61000-4-6
IEC 61000-4-8, IEC 61000-4-11

Safety Standards

UL 60950 APPROVAL
CSA 60950 APPROVAL
CE Marking

Environments

Operating Temperature -15 ~ 50°C, Ambient
Operating Humidity 5 ~ 95% RH, No Condensing
Storage Temperature -20 ~ 85°C, Ambient
Vibration 2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 110VAC input.
 4. Ripple & Noise is measured by using a 0.1uF/630V metalized capacitor & a 47uF electrolytic capacitor parallel on the test point, at rated load and 110VAC input.
 5. Efficiency is measured at rated load and 110VAC input.
 6. Hold-up time is measured at rated load and 110VAC input.
 7. With ● are CE approval only.