

■ Features:

- ✓ Universal AC input/ Full range
- ✓ 5V/12V/15V no load power consumption<0.5W
- ✓ All series with **conformal coating**
- ✓ High Efficiency, and High reliability
- ✓ Output protections: OLP/OVP/SCP
- ✓ Wide operating ambient temperature (-20°C~70°C)
- ✓ All using 105°C long life electrolytic capacitors.
- ✓ 100% full load burn-in test
- ✓ 3 years warranty



SPECIFICATIONN

MODEL		PD-25-S3.3	PD-25-S5	PD-25-S12	PD-25-S15	PD-25-S24	
OUTPUT	DC Output	3.3V	5V	12V	15V	24V	
	Rated Current	6A	5A	2.1A	1.7 A	1.1A	
	Current Range	Note 1	0~6A	0~5A	0~2.1A	0~1.7A	0~1.1A
	Ripple and Noise	-20~70°C	<50mV	<50mV	<120mV	<120mV	<120mV
	Note 2						
	Voltage ADJ. Range		3.0~3.6V	4.4~5.5V	10.0~13.0V	13.8~16.1V	20.7~26.7V
	Voltage Accuracy		±2.0%	±2.0%	±1.0%	±1.0%	±1.0%
	Line Regulation		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Load Regulation		±2.0%	±2.0%	±1.0%	±1.0%	±1.0%
	Set-up Time		<2.0S (115Vac input, Full load); <1.0S (230Vac input, Full load)				
	Hold up Time		>14mS(115Vac input, Full load); >30mS(230Vac input, Full load)				
	Temperature Coefficient		±0.03%/°C				
Overshoot and Undershoot		<5.0%					
INPUT	Voltage Range	88Vac~264Vac, 124~370Vdc					
	Frequency Range	47Hz~63Hz					
	Efficiency (Typical)	115Vac input	70%	76%	80%	82%	84%
		230Vac input	71%	78%	82%	83%	85%
	AC Current (max.)	0.7A	0.7A	0.7A	0.7A	0.7A	
	Inrush Current (Typical)	<20A@115Vac <40A@230Vac Cold start					
Leakage Current	input—output:<0.25mA Input—PG:<0.75mA						
PROTECTION	Over Load	105%~150% of rated output current, hiccup mode,auto recovery					
	Over Voltage	05%~150% of rated output voltage, Constant Voltage					
	Short Circuit	long-term mode, auto recovery					
ENVIRONMENT	Operating amb. Temp. & Hum.	-20°C~70°C; 20%~90%RH No condensing((refer to the derating curve)					
	Storage Temp. & Hum.	-40°C~85°C; 10%~95%RH No condensing					
SAFETY & EMC Note 3	Safety Standards	UL60950-1; EN60950-1: 2006					
	Withstand Voltage	Primary-Secondary:3.0KVac; ≤10mA .Primary-PG:1.5KVac; ≤10mA. Secondary-PG:0.5KVDC;≤10mA.					
	Isolation Resistance	≥100M ohms					
	EMI Conduction&Radiation	Compliance to EN55022(CISPR22) ClassB					
	Harmonic Current	Compliance to EN61000-3-2,-3					
OTHERS	EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11;ENV50204,light industry level,criteriaA					
	MTBF (MIL-HDBK-217F)	More than 200,000Hrs (25°C, Full load)					
	Dimension (L*W*H)	79×51×28mm					
	Packing	8PCS/CTN, 10.4KGS, 0.03CBM					
NOTE	Cooling method	Cooling by free air convection					
		1. All parameters NOT specially mentioned are measured at rated input, rated load and 25°C of ambient temperature. 2. Measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 uF & 47uF parallel capacitor.					