

CV-200RC

200W Aluminum Rainproof Power Supply

Rainproof Design, Accord with IP21
 Special Aluminum Case, Excellent heat-dissipating, high reliability
 Protection: Over Load/ Short Circuit
 100% full load burn-in-test
 1 year warranty
 Size: 219×102×49mm



AC input voltage range..... 176-264VAC
 Input frequency.....47-63Hz
 AC inrush current..... Cold start, 60A/ 230VAC
 Line regulation (full load)±1%
 Output over load protection.....hiccup mode, auto-recovery
 Rise. Hold up time 100mS, 10mS at full load
 Withstand voltage..... I/P-O/P, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC
 Working temperature.....-20°C~+60°C (refer to temperature derating curve)
 Storage temperature..... -40°C~+85°C @100% 20%~95%RH (non-condensing)
 Safety standards.....GB4943, UL60950-1, EN60950-1
 EMC standards..... GB9254, EN55022 class A
 Cooling method.....Forced air cooling by Built-in DC fan

Model No.	DC output	Load regul.	R&N	Effi.
CV-200RC-12	12V, 0~16.6A	±1%	300mV	85%
CV-200RC-24	24V, 0~8.3A	±1%	300mV	87%
CV-200RC-36	36V, 0~5.6A	±1%	300mV	88%
CV-200RC-48	48V, 0~4.2A	±1%	400mV	88%