

## Product Model: CV-400RD

### 400W Aluminum Rainproof Power Supply

Special Aluminum Case, Excellent heat-dissipating, High reliability

Protection: Over Load/ Short Circuit

100% full load burn-in-test

1 year warranty

Size: 224x124x60mm

AC input voltage range..... 176-264VAC

Input frequency.....47-63Hz

AC inrush current.....Cold start, 60A/ 230VAC

Line regulation(full load) .....±1%

Output over load protection.....hiccup mode, auto-recovery

Rise. Hold up time ..... 100mS, 10mS at full load

Withstand voltage..... I/P-O/P, I/P-FG:1.5KVAC, O/P-FG: 0.5KVAC

Working temperature.....-20°C~+60°C ( refer to temperature derating curve )

Storage temperature..... -40°C~+85°C@100% 20%~95%RH (non condensing)

Safety standards.....GB4943, UL60950-1, EN60950-1

EMC standards..... GB9254, EN55022 class A

Cooling method.....Forced air cooling by Built-in DC fan

Model No.	DC output	Load regul.	R&N	Effi.
CV-400RC-12	12V, 0~33A	±1%	150mV	83%
CV-400RC-24	24V, 0~16.6A	±1%	200mV	85%
CV-400RC-36	36V, 0~11A	±1%	300mV	86%
CV-400RC-48	48V, 0~8.3A	±1%	400mV	86%

