

Model: HT-350 Series

350W Single Output DC-DC Switching Power Supply

- ✓ Low Cost, High Reliability
- ✓ Low Power Consumption
- ✓ Built-In EMI Filter
- ✓ 2:1 Wide Input Range
- ✓ 1500VDC I/O Isolation
- ✓ Forced Air Cooling By Built-In DC Fan
- ✓ Protections: Over Load/ Over Voltage/ Over Temp./ Short Circuit
- ✓ 1 Year Warranty



DC Adjustment Range.....5V: 4.5~5.5V, 12V: 11~16V, 24V: 23~30V, 48V: 43~53V

Line Regulation.....≤0.5%

Output over Load Protection.....105%-135% Shut Off, Re-Power On To Recover

Output Over Voltage Protection...110%~167% Rated Output Voltage

Output Short Circuit Protection...Shut Off, Re-Power On To Recover

Hi-pot Isolation.....I/P-O/P, I/P-FG: 1.5KVDC, O/P-FG: 0.5KVDC, 1 min

Isolation Resistance.....100MΩ (min.) at 500VDC

Operating Temperature Range...-10°C to 50°C@100%, -20°C@80%, 60°C@60% load

Storage Temperature Range.....-40°C to +85°C, 0 to 95%RH (None Condensing)

Safety Standards.....Design Refer To UL60950

EMC Standards.....Design Refer To FCC Part 15 J

Cooling Method.....Forced Air Cooling By Built-In DC Fan

Weight.....1.1Kg/pc

Product Model	DC Input	DC Output	Load Regul.	R&N	Efficiency
HT-350-24-5	18~36V	5V, 0~57A	1%	75mV	75%
HT-350-24-12	18~36V	12V, 0~27.5A	0.5%	100mV	81%
HT-350-24-24	18~36V	24V, 0~14.6A	0.5%	150mV	81%
HT-350-24-48	18~36V	48V, 0~7.3A	0.5%	200mV	85%
HT-350-48-5	36~72V	5V, 0~57A	1%	75mV	77%
HT-350-48-12	36~72V	12V, 0~27.5A	0.5%	100mV	82%
HT-350-48-24	36~72V	24V, 0~14.6A	0.5%	150mV	82%
HT-350-48-48	36~72V	48V, 0~7.3A	0.5%	200mV	83%
HT-350-110-5	72~144V	5V, 0~57A	1%	75mV	79%
HT-350-110-12	72~144V	12V, 0~27.5A	0.5%	100mV	84%
HT-350-110-24	72~144V	24V, 0~14.6A	0.5%	150mV	88%
HT-350-110-48	72~144V	48V, 0~7.3A	0.5%	200mV	90%